

## RAKU-TOOL<sup>®</sup> Ancillaries for Epoxy and Polyurethane Systems

PC - Rev.-Status: 01- 2011/11/10

Page 1 of 2

<b>AC-9001</b>	<b>Mineral Filler</b> Color: White Density: 2.7 g/cm <sup>3</sup> Bulk density: 1.0 g/cm <sup>3</sup> Can be used with Epoxy and Polyurethane Systems Packaging: 18 kg
<b>AC-9002</b>	<b>Light Mineral Filler</b> Color: Gray Density: 0.60-0.85 g/cm <sup>3</sup> Bulk density: 0.35 – 0.4 g/cm <sup>3</sup> Can be used with Epoxy and Polyurethane Systems Packaging: 20 kg
<b>AC-9004</b>	<b>Inorganic Filler</b> Color: White Density: 2.4 g/cm <sup>3</sup> Bulk density: 1.6 g/cm <sup>3</sup> Can be used with Epoxy and Polyurethane Systems Packaging: 20 kg, 1000 kg
<b>AC-9101</b>	<b>PVA Mold Sealer</b> Film forming Poly-Vinyl-Alcohol (P.V.A.) release agent, which can also be used as sealer for porous surfaces. Color: Green Packaging: 1 kg, 4.5 kg
<b>AC-9102</b>	<b>Paste Release Agent</b> Wax based release agent for general applications. Can be polished to obtain a high gloss. Color: White Packaging: 12x1 kg

**RAKU-TOOL<sup>®</sup> Ancillaries  
 for Epoxy and Polyurethane Systems**

PC - Rev.-Status: 01- 2011/11/10

Page 2 of 2

**AC-9103****Liquid Release Agent**

Wax based liquid release agent for the release of general and detailed mold surfaces. Can be polished to obtain a high gloss.

Color: White

Packaging: 6x0.75 kg, 4x3.75 kg

**AC-9500****Wax Sheets**

Self adhesive and temperature resistant to 135-140°C

Color: Yellow

Available Thicknesses:	Number of wax sheets per pack:	Sales unit:
0.50 mm	10	10
0.75 mm	8	10
0.80 mm	8	10
1.00 mm	8	10
1.25 mm	8	10
1.50 mm	8	10
1.75 mm	8	10
2.00 mm	8	10
2.50 mm	6	10
3.00 mm	4	10
4.00 mm	4	10
5.00 mm	3	10

**Storage**

Original containers should be kept tightly sealed and stored at ambient temperatures (15°C to 30°C) in a dry place. If properly stored the products have the shelf-life indicated on the product label.

Partly used containers should always be sealed appropriately and used up as soon as possible.

**Handling Precautions**

Good workplace ventilation is to be ensured during processing. At the same time, the employer's liability insurance association's industrial hygiene safety regulations regarding the handling of reaction resins and their hardeners are to be observed. Please take heed of the appropriate safety data sheets.